

LRD-0980-PF SERIES INFORMATION SHEET

The LRD-0980 Series of Collimated Diode (Semiconductor) Lasers are ideal for applications requiring a wavelength of around 980nm and a wide range of output power levels from 50mW to 1W with a high level of long-term output power stability and long operating lifetime at an aggressively competitive cost.

These lasers are commonly used for communications research, machine vision, scientific applications involving spectral analysis, biology research, and a broad spectrum of other applications. The driver is available as a complete FDA-compliant system or as an O.E.M. component with significantly reduced dimensions in 80-260VAC, 12VDC, or 5VDC input voltage.

Available with onboard and remote on/off control as well as a wide array of output power and stability levels, Laserglow products are currently being used by some of the World's top universities and other prominent research facilities.

KEY FEATURES:

- Air cooled – no need for water cooling or external chiller
- Lightweight, compact design
- Efficient Diode Laser technology runs on standard AC power (85 – 264 V, 47 – 63 Hz)
- >10,000 hours continuous maintenance-free operating life
- 30kHz TTL modulation (input via BNC connector)¹
- 30kHz analog modulation (input via BNC connector)²
- Adjustable output power via lockable dial
- LED display showing LD current, laser cavity temperature
- FDA CDRH Compliant Class IIIb / Class IV enclosure
- 48-hour replacement coverage available for an additional fee

CUSTOM OPTIONS:

- Fiber coupling – The LRD-0980 series can be fiber-coupled to the customer's choice of fiber optic cable; the most common types of connectors are FC and SMA-905. Unless otherwise specified, armored fiber will be used to avoid damage during transport and use. Please see the fiber coupling efficiency chart on Page 4 to ensure sufficient output power for your application.
- Custom optics – The output beam can be shaped per the customer's requirements, including customizable beam diameter, divergence and ellipticity. Line-generating optics can be installed to match the customer's requirements.
- Operating Voltage – By special request, the LRD-0980 series can be configured to run on either AC or DC current at nearly any voltage that the customer requires.

¹ Output may not reach full power as per specifications when modulating at this speed

² Output power variation adjustment may not be linear with dial



SPECIFICATIONS: (Please see model number/ SKU reference table on Page 4 for full model number/SKU.)

Dimensional Drawing Reference (see below)		A	B
Model	LRD-0980-	PFR-_____-__	PFS-_____-__
Wavelength (nm)		980 (+/-5)	980 (+/-5)
Actual Centre Wavelength (nm)		978	978
Output Power		>100 mW >500 mW >1 W >2 W	>3 W >4 W
Output Power Stability ₃ (RMS/4 hrs.)		<5%, <3%, <1%	<5%, <3%, <1%
Warm-up time (min)		<5	<5
M ² Factor		<20	<20
Beam Divergence (mrad)		<3	<3
Beam dimensions at aperture (mm)		~5 X 8	~5 X 8
Beam height from base (mm)		24.8	29
Polarization ratio		>50:1	>50:1
Pointing stability after warm-up (mrad)		<0.05	<0.05
Operating temperature (°C)		10-35	10-35
Transverse Mode		Near TE00	Near TE00
MTTF (hours)		>10,000	>10,000
Limited Warranty		1 year	1 year
Operating Mode		CW	CW
Power Supply		90-264VAC	90-264VAC

³ Stability values guaranteed only after operating continuously at full power for a minimum of 15 minutes.

DIMENSIONAL DRAWINGS (please refer to model number in specifications chart above):

A LRD-0980-PFR-_____ - _____	
Weight: 0.6kg	Weight: 1.5kg
B LRD-0980-PFS-_____ - _____	
Weight: 0.6kg	Weight: 1.5kg

FIBER COUPLING OPTIONS:

1. Fiber connector only: Please specify connector type (SMA-905 or FC) and the core diameter of the fiber you will be using.
2. Permanent coupling: Fiber cable will be aligned for maximum efficiency and permanently bonded in place to ensure reliability.
3. Detachable coupling: Fiber cable will be removable from coupler and can be swapped for a different cable. As this allows some variability in alignment, coupling efficiency will be slightly less than outlined below.

Fiber Type:	Single Mode	Multi Mode	Multi Mode	Multi Mode
Core Diameter:	4-9µm	≥100µm	≥200µm	≥400µm
Coupling Efficiency:	[not available on Diode lasers, only on DPSS lasers]	>30%	>60%	>80%
Example using >100mW laser:	-N/A-	>30mW fiber output	>60mW fiber output	>80mW fiber output

FOR FURTHER INQUIRIES PLEASE CONTACT:

LASERGLOW TECHNOLOGIES

216-5 Adrian Ave.
Toronto, ON, M6N5G4
Canada

Tel. (416) 729-7976

Fax (480) 247-4864

sales@laserglow.com

www.laserglow.com