

## LRD-0808 Collimated Diode Laser System

### Laserglow Part Number: D80010XSL

This model is listed as **inactive** in our product database. Stock may be limited, and availability is subject to change without notice.



#### Similar Products:

For information about the other lasers in this product family visit:

<http://www.laserglow.com/D80>

#### Ordering:

Order Online Now or Request Quote:

<http://www.laserglow.com/D80010XSL>

#### Series Specifications:

|                    |        |
|--------------------|--------|
| Nominal Wavelength | 808 nm |
| Output Type        | CW     |
| Laser Source Type  | Diode  |



#### Overview:

The LRD-0808 Series of Collimated Diode (Semiconductor) Lasers are ideal for applications requiring a wavelength of around 808 nm and a wide range of output power levels from 10 mW to 10 W with a high level of long-term output power stability and long operating lifetime at an aggressively competitive cost.

These lasers are commonly used for scientific applications involving spectral analysis, biology research, materials processing, communications research, and wide range of industrial processes. The driver is available as a complete FDA-compliant system or as an O.E.M. component with significantly reduced dimensions.

Available with on-board and remote on/off control as well as a wide array of output power and stability levels, Laserglow products are currently being used by some of the world's top universities and other prominent research facilities.

#### Key Features:

- Air cooled - no need for water cooling or external chiller
- Lightweight, compact design
- Efficient Diode Laser technology runs on standard AC power (85 - 264 V, 47 - 63 Hz)
- >10,000 hours continuous maintenance-free operating life
- FDA CDRH Compliant Class IIb / Class IV enclosure
- 48-hour replacement coverage available for an additional fee on specific models

#### Package Includes:

- Laser Head
- Driver/Power Supply
- Power Cable
- BNC Connector (LabSpec models only)
- Keys, Safety Interlock
- Hard-shell Carrying Case

## Specifications:

This spec sheet has been generated specifically for part number D80010XSL, per your request, and data for the entire series is also displayed for your reference. The specs which are specific to D80010XSL have been highlighted below in **red + bold**.


|  |  |                               |                             |                           |                           |
|--|--|-------------------------------|-----------------------------|---------------------------|---------------------------|
| Output Power (mW)                        | <b>&gt;10, &gt;100, &gt;300, &gt;500</b> | >100, >1000, >2000            | >1500                       | >5000                     | >8000, >10000, >12000     |
| Output Power Stability (%RMS/4h)         | <1, <3, <b>&lt;10</b>                    | <1, <3, <10                   | <1                          | <1, <3                    | <1, <3                    |
| Central Wavelength (nm)                  | <b>808</b>                               | 808                           | 808                         | 808                       | 808                       |
| Wavelength Tolerance (+/- nm)            | <b>3</b>                                 | 3                             | 3                           | 3                         | 3                         |
| Divergence (mrad, full angle)            | <b>&lt;1</b>                             | <3                            | <120x240                    | <3                        | <3                        |
| Beam Dimensions (mm, 1/e <sup>2</sup> )  | <b>3.5</b>                               | 5x8                           |                             | 5x8                       | 5x8                       |
| Warm-up Time (minutes)                   | <b>5</b>                                 | 5                             | 5                           | 5                         | 5                         |
| Operating Temperature Range (°C)         | <b>10 to 35</b>                          | 10 to 35                      | 10 to 35                    | 10 to 35                  | 10 to 35                  |
| Max. Analog Modulation Freq. (Hz)        | 30000                                    | 30000                         | 30000                       | 30000                     | 30000                     |
| Max. TTL Modulation Freq. (Hz)           | <b>10000</b> , 30000                     | 10000, 30000                  | 30000                       | 30000                     | 30000                     |
| Modulation Input Signal                  | <b>0-5 VDC</b>                           | 0-5 VDC                       | 0-5 VDC                     | 0-5 VDC                   | 0-5 VDC                   |
| Total Power Consumption (W)              | <b>14, 16</b>                            | 14, 19, 26                    |                             | 95                        | 140                       |
| Max. Power Input Duty Cycle              | <b>100%</b>                              | 100%                          | 100%                        | 100%                      | 100%                      |
| Standard Warranty (months)               | <b>12</b>                                | 12                            | 12                          | 12                        | 12                        |
| MTTF (operational hours)                 | <b>10000</b>                             | 10000                         | 10000                       | 10000                     | 10000                     |
| Weight of Product or Laser Head (kg)     | <b>0.6</b>                               | 0.6                           | 5.4                         | 0.9                       | 2.6                       |
| Beam Height from Base Plate (mm)         | <b>24.8</b>                              | 24.8                          |                             | 29                        | 68.2                      |
| Dimensions of Product or Laser Head (mm) | <b>140.7 (l) x 73 (w) x 46.2 (h)</b>     | 140.7 (l) x 73 (w) x 46.2 (h) | 314 (l) x 290 (w) x 134 (h) | 155 (l) x 77 (w) x 60 (h) | 240 (l) x 99 (w) x 94 (h) |


CW: All specifications are based on performance at full output power and after the specified warmup period. Output characteristics may change if the laser is run at a different power level.

Q-Switched: Specifications are based on the laser pulsing at the specified design frequency. Output characteristics may change if the laser is run at a different frequency.

## Power Supply Options:

These lasers are available with several different power supply options. The model that you have selected is highlighted below, and any other options are shown for easy reference.

|   |                          |                                   |
|---|--------------------------|-----------------------------------|
|  | Power Supply Type:       | <b>SR</b>                         |
|   | Input Power              | <b>85v to 264v</b>                |
|   | Power Supply Weight (kg) | <b>1.2</b>                        |
|   | Dimensions (mm)          | <b>133 (l) x 130 (w) x 65 (h)</b> |

|   |                          |                            |                             |                             |
|---|--------------------------|----------------------------|-----------------------------|-----------------------------|
|  | Power Supply Type:       | <b>FR</b>                  | <b>FN</b>                   | <b>FT</b>                   |
|   | Input Power              | 85v to 264v                | 85v to 264v                 | 85v to 264v                 |
|   | Power Supply Weight (kg) | 1.5                        | 2.6                         | 2.6                         |
|   | Dimensions (mm)          | 154 (l) x 155 (w) x 95 (h) | 268 (l) x 145 (w) x 106 (h) | 268 (l) x 145 (w) x 106 (h) |

|   |                          |                       |
|---|--------------------------|-----------------------|
|  | Power Supply Type:       | <b>II</b>             |
|   | Input Power              | 85v to 264v           |
|   | Power Supply Weight (kg) | 0                     |
|   | Dimensions (mm)          | 0 (l) x 0 (w) x 0 (h) |

\*Power supply may not be exactly as shown, see dimensional drawings on next 2 pages.

\*Dimensions for fiber-integrated (I\_) include laser head packaged inside.

## Regulatory Classification:

The model you have selected (D80010XSL) requires the following safety label(s):









Dimensional Drawing - Power Supply Form Factor: SR:



## Accessories:

The most popular accessories for model D80010XSL are shown below. For additional details regarding these or other accessories please see our website or contact us directly.

| Part Number  | Description   |  |
|--|---|--|
| <br>AFS2002XX | Armored Fiber With SMA 905 Connectors 200um Core Multimode 2 m length<br>Full Details: <a href="http://www.laserglow.com/AFS">www.laserglow.com/AFS</a>   |  |
| <br>AGF80859X | LSG-808-NF-6 Fit-Over Safety Goggles 808nm<br>Output: OD 6+ at 800-818 nm<br>CE Certified<br>Full Details: <a href="http://www.laserglow.com/AGF">www.laserglow.com/AGF</a>                               |  |
| <br>ACFNIRHXA | FC/PC Fiber Coupler/Collimator for IR wavelengths (700 to 1000 nm) (installed and aligned)<br>11mm diameter input lens<br>Full Details: <a href="http://www.laserglow.com/ACF">www.laserglow.com/ACF</a>  |  |
| <br>ACSNIRHXA | SMA-905 Fiber Coupler/Collimator for IR wavelengths (700 to 1000nm) (installed and aligned)<br>11mm diameter input lens<br>Full Details: <a href="http://www.laserglow.com/ACS">www.laserglow.com/ACS</a> |  |

## FOR MORE INFORMATION PLEASE CONTACT:

LASERGLOW TECHNOLOGIES  
99 Ingram Dr. Unit B, North York, ON, Canada M6M2L7  
Tel. (416) 729-7976 Fax (716) 322-3510  
[sales@laserglow.com](mailto:sales@laserglow.com) [www.laserglow.com](http://www.laserglow.com)

E&OE: Data included in this sheet may be subject to change without notice.

Please confirm critical specifications with our staff prior to ordering.