

Horizon Series Horizon Series Self-Levelling Alignment Laser

**Laserglow Part Number:
BALG5XXX**

Similar Products:

For information about the other lasers in this product family visit:

<http://www.laserglow.com/BAL>

Ordering:

Order Online Now or Request Quote:

<http://www.laserglow.com/BALG5XXX>



Overview:

The Horizon Green Standard 5 Line Laser - BALG5 is a self-levelling, multi-line laser level which generates very bright, highly visible green lines. The BALG5 is classified as a Cross & Line level instrument that generates one horizontal & four vertical lines that create an overhead cross. A red downward pointing plumb dot can be used as a setting-out reference spot. This model is ideal for indoor use and can also be used outdoors with the included receiver.

The BALG5 comes with a digital display and USB port for mobile-charging!

Key Features:

- **Starting at: \$499**
- **Output Color:** Green
- **Expected Life:** 10000 hours
- **Projection Type:** 4 Vertical, 1 Horizontal, 1 red plumb dot - 4V1H1D
- **Key Feature:** Projects green self-levelling lines for high precision interior and outdoor applications.
- **Minimum achievable line thickness:** 0.25 mm at 30 cm
- **Package Includes:** Self-levelling laser with carrying case, magnetic ceiling target and receiver.

How It Works:

- The Multi-Line Horizon Series BALG5 is a multi-featured Cross Line Laser suitable for both Indoor & Outdoor use.
- Green light is three to five times more visible than red light, so this model is recommended for applications requiring **high visibility**.
- The BALG5 can be placed on any firm surface or mounted on our many laser accessories via its base 5/8" thread.
- The BALG5 has an accurate, pendulum system for quick self-levelling.
- When not in self-levelling range, the BALR5 indicates by flashing the laser beams On & Off. Once within self-levelling range, the unit stops flashing.
- The Laser has one horizontal & 4 vertical lines with one downward pointing red plumb dot, where the 4 vertical lines cross create an overhead cross.
- With a smooth horizontal rotating mechanism and fine adjustment knobs for convenience, the base enables you to set vertical line positions with ease.
- The Receiver is essential for outdoor use, but it can also be used indoors in bright conditions or where long range is required.
- The BALG5 operates with a rechargeable battery pack or 4 AA batteries, and is the only model that comes with a digital display and USB charging option.

Common Applications:

Carpentry, decking, electrical sockets, switches & lighting, suspended ceiling construction, flooring, foundations leveling, kitchen and bedroom fittings,

machinery installation, painting & decorating, partitioning, shelving, shopfitting, stud walls, tiling, plumbing, and bi-fold doors installation.

Specifications:

This spec sheet has been generated specifically for part number BALG5XXXX, per your request, and data for the entire series is also displayed for your reference. The specs which are specific to BALG5XXXX have been highlighted below in **red + bold**.

Product	BALGR	BALRR	BALR2	BALR5	BALG5	BALR8	BALG8
Output Color	Green (High Visibility)	Red	Red	Red	Green (High Visibility)	Red	Green (High Visibility)
Number of Vertical Lines			1	4	4	4	4
Number of Horizontal Lines	1	1	1	1	1	4	4
Accuracy	+/- 1.0mm / 10M	+/- 1.0mm / 10M	+/- 1.0mm / 5M	+/- 1.0mm / 5M	+/- 1.0mm / 5M	+/- 1.0mm / 10M	+/- 1.0mm / 10M
Projection Angle ()	360 degree scan (horizontal or vertical)	360 degree scan (horizontal or vertical)	Horizontal >100 Vertical >120	Horizontal >100 Vertical >120	Horizontal >100 Vertical >120	Horizontal 360 Vertical >120	Horizontal 360 Vertical >120
Self-leveling range ()	+/- 5	+/- 5	+/- 3	+/- 3	+/- 3	+/- 3.5	+/- 3.5
Plumb Dot	Yes	Yes		Yes	Yes	Yes	Yes
Plumb Dot Color	Red	Red		Red	Red	Red	Red
Overhead Dot	Yes	Yes					
Overhead Dot Color	Green	Red					
Receiver Compatible	Yes	Yes		Yes	Yes		
Water Resistant	Yes	Yes					
Carrying Case Included	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Can Run on AC Power	Yes	Yes				Yes	Yes
Tripod/Bracket Thread	5/8"-11	5/8"-11	5/8"-11	5/8"-11	5/8"-11	5/8"-11	5/8"-11
Output Power (mW)	<5	<5	>10	>10	>10	>10	>10
IEC Safety Class	3R	3R	2M	2M	2M	2M	2M
Standard Warranty (months)	6	6	6	6	6	6	6
MTTF (operational hours)	10000	10000	10000	10000	10000	10000	10000
Power Source	4x C batteries	4x C batteries	2x AA batteries	4x AA batteries	Rechargeable battery pack or 4x AA batteries	4x AA batteries	Rechargeable battery pack
Battery Life	12 hours	12 hours	12 hours	12 hours	24 hours	12 hours	24 hours
Weight of Product or Laser Head (kg)	2	2	0.45	0.95	1.13	1.61	1.61
Dimensions of Product or Laser Head (mm)	160 (l) x 160 (w) x 185 (h)	160 (l) x 160 (w) x 185 (h)	92 (l) x 92 (w) x 130 (h)	116 (l) x 124 (w) x 170 (h)	124 (l) x 116 (w) x 175 (h)	160 (l) x 140 (w) x 220 (h)	160 (l) x 140 (w) x 220 (h)
Power Supply	4 x AA batteries, 4 x C Batteries, 7.4 V 3100 mAh Li-ion Battery Pack, Mobile Power Lithium Battery Pack	4 x AA batteries, 4 x C Batteries, 7.4 V 3100 mAh Li-ion Battery Pack, Mobile Power Lithium Battery Pack	4 x AA batteries, 4 x C Batteries, 7.4 V 3100 mAh Li-ion Battery Pack, Mobile Power Lithium Battery Pack	4 x AA batteries, 4 x C Batteries, 7.4 V 3100 mAh Li-ion Battery Pack, Mobile Power Lithium Battery Pack	4 x AA batteries, 4 x C Batteries, 7.4 V 3100 mAh Li-ion Battery Pack, Mobile Power Lithium Battery Pack	4 x AA batteries, 4 x C Batteries, 7.4 V 3100 mAh Li-ion Battery Pack, Mobile Power Lithium Battery Pack	4 x AA batteries, 4 x C Batteries, 7.4 V 3100 mAh Li-ion Battery Pack, Mobile Power Lithium Battery Pack

CW: All specifications are based on performance at full output power and after the specified warmup period. Output characteristics may change if the laser is run at a different power level.

Q-Switched: Specifications are based on the laser pulsing at the specified design frequency. Output characteristics may change if the laser is run at a different frequency.

Specifications Page 2:

This spec sheet has been generated specifically for part number BALG5XXXX, per your request, and data for the entire series is also displayed for your reference. The specs which are specific to BALG5XXXX have been highlighted below in **red + bold**.


Laser Form Factor

Power Supply Options:

The Horizon series of self-levelling alignment lasers are battery-operated. The BALR2 requires two alkaline or Ni-MH AA batteries. The BALR5 requires four alkaline or Ni-MH AA batteries. The BALG5 includes a rechargeable 4000 mAh lithium-ion battery pack, which is recharged via an included microUSB cable and wall adaptor. The BALG5 can also run on four alkaline or Ni-MH AA batteries.


Regulatory Classification:

The model you have selected (BALG5XXXX) requires the following safety label(s):



Accessories:

The most popular accessories for model BALG5XXXX are shown below. For additional details regarding these or other accessories please see our website or contact us directly.

Part Number	Description	
 ATP006XXX	1.2 Meter Elevator Tripod 5/8-11 Thread For Horizon Laser Levels Full Details: www.laserglow.com/ATP	
Image Coming Soon! BAMLG0XXX	Green Line Receiver for 5 Line Laser Levels Full Details: www.laserglow.com/BAM	Included With Laser
Image Coming Soon! ARLMCTXXX	Magnetic Ceiling Target for Laser Levels Full Details: www.laserglow.com/ARL	Included With Laser

FOR MORE INFORMATION PLEASE CONTACT:

LASERGLOW TECHNOLOGIES
99 Ingram Dr. Unit B, North York, ON, Canada M6M2L7
Tel. (416) 729-7976 Fax (716) 322-3510
sales@laserglow.com www.laserglow.com

E&OE: Data included in this sheet may be subject to change without notice.

Please confirm critical specifications with our staff prior to ordering.