

Horizon Series Horizon Series Self-Levelling Alignment Laser

**Laserglow Part Number:
BALR5XXX**

Similar Products:

For information about the other lasers in this product family visit:

<http://www.laserglow.com/BAL>

Ordering:

Order Online Now or Request Quote:

<http://www.laserglow.com/BALR5XXX>

Laserglow Technologies™
H O R I Z O N



Overview:

The Horizon Red Standard 5 Line Laser - BALR5 is an accurate, self levelling instrument which generates bright, visible red (thin) lines. There is one horizontal line, 4 vertical lines which create an overhead cross and a downward pointing dot displaying plumb. The horizontal & vertical lines can be switched ON/Off independently or all used together. This model is ideal for indoor use and can also be used outdoors with the included receiver.

Key Features:

- **Starting at: \$299**
- **Output Color:** Red
- **Expected Life:** 10000 hours
- **Projection Type:** 4 Vertical, 1 Horizontal, 1 plumb dot - 4V1H1D
- **Key Feature:** Projects red self-levelling lines for high precision applications.
- **Minimum achievable line thickness:** 0.25 mm at 30 cm
- **Package Includes:** Self-levelling laser with carrying case, wall-mount, magnetic ceiling target and receiver.

How It Works:

- The Multi-Line Horizon Series BALR5 is a multi-featured Cross Line Laser suitable for both Indoor & Outdoor use.
- To enable it to operate Outdoors, the pulsed output setting and included laser receiver allow good visibility.
- The BALR5 has an accurate, pendulum system for quick self-levelling.
- When not in self-level range, the BALR5 indicates by flashing the laser beams On & Off. Once within level range, the unit will stop flashing.
- The Laser has one horizontal & 4 vertical lines with one downward plumb dot, where the 4 vertical lines cross above.
- With a smooth horizontal rotating mechanism and fine adjustment knob for convenience, the base enables you to set vertical line positions with ease.
- The Receiver is essential for outdoor use, but it can also be used indoors in bright conditions or where long range is required.

Common Applications:

Carpentry, Electrical sockets, switches & lighting, Suspended Ceiling Construction, Foundations leveling, Kitchens and Bedroom fittings, Machinery installation, Painting & Decorating, Partitioning, Shelving, Shopfitting, Stud walls, Tiling, and Bi-fold Doors installation.

Specifications:

This spec sheet has been generated specifically for part number BALR5XXXX, per your request, and data for the entire series is also displayed for your reference. The specs which are specific to BALR5XXXX have been highlighted below in **red + bold**.

| Product | BALRR | BALGR | BALR2 | BALR5 | BALR8 | BALG8 |
|--|---|---|---|--|---|---|
| Output Color | Red | Green (High Visibility) | Red | Red | Red | Green (High Visibility) |
| Number of Vertical Lines | | | 1 | 4 | 4 | 4 |
| Number of Horizontal Lines | 1 | 1 | 1 | 1 | 4 | 4 |
| Accuracy | +/- 1.0mm / 10M | +/- 1.0mm / 10M | +/- 1.0mm / 5M | +/- 1.0mm / 5M | +/- 1.0mm / 10M | +/- 1.0mm / 10M |
| Projection Angle (°) | 360 degree scan (horizontal or vertical) | 360 degree scan (horizontal or vertical) | Horizontal >100 Vertical >120 | Horizontal >100 Vertical >120 | Horizontal 360 Vertical >120 | Horizontal 360 Vertical >120 |
| Self-leveling range (°) | +/- 5 | +/- 5 | +/- 3 | +/- 3 | +/- 3.5 | +/- 3.5 |
| Plumb Dot | Yes | Yes | | Yes | Yes | Yes |
| Plumb Dot Color | Red | Red | | Red | Red | Red |
| Overhead Dot | Yes | Yes | | | | |
| Overhead Dot Color | Red | Green | | | | |
| Receiver Compatible | Yes | Yes | | Yes | | |
| Water Resistant | Yes | Yes | | | | |
| Carrying Case Included | Yes | Yes | Yes | Yes | Yes | Yes |
| Can Run on AC Power | Yes | Yes | | | Yes | Yes |
| Tripod/Bracket Thread | 5/8"-11 | 5/8"-11 | 5/8"-11 | 5/8"-11 | 5/8"-11 | 5/8"-11 |
| Output Power (mW) | <5 | <5 | >10 | >10 | >10 | >10 |
| IEC Safety Class | 3R | 3R | 2M | 2M | 2M | 2M |
| Standard Warranty (months) | 6 | 6 | 6 | 6 | 6 | 6 |
| MTTF (operational hours) | 10000 | 10000 | 10000 | 10000 | 10000 | 10000 |
| Power Source | 4x C batteries | 4x C batteries | 2x AA batteries | 4x AA batteries | 4x AA batteries | Rechargeable battery pack |
| Battery Life | 12 hours | 12 hours | 12 hours | 12 hours | 12 hours | 24 hours |
| Weight of Product or Laser Head (kg) | 2 | 2 | 0.45 | 0.95 | 1.61 | 1.61 |
| Dimensions of Product or Laser Head (mm) | 160 (l) x 160 (w) x 185 (h) | 160 (l) x 160 (w) x 185 (h) | 92 (l) x 92 (w) x 130 (h) | 116 (l) x 124 (w) x 170 (h) | 160 (l) x 140 (w) x 220 (h) | 160 (l) x 140 (w) x 220 (h) |
| Power Supply | 4 x AA batteries, 4 x C Batteries, 7.4 V 3100 mAh Li-ion Battery Pack | 4 x AA batteries, 4 x C Batteries, 7.4 V 3100 mAh Li-ion Battery Pack | 4 x AA batteries, 4 x C Batteries, 7.4 V 3100 mAh Li-ion Battery Pack | 4 x AA batteries, 4 x C Batteries, 7.4 V 3100 mAh Li-ion Battery Pack | 4 x AA batteries, 4 x C Batteries, 7.4 V 3100 mAh Li-ion Battery Pack | 4 x AA batteries, 4 x C Batteries, 7.4 V 3100 mAh Li-ion Battery Pack |

CW: All specifications are based on performance at full output power and after the specified warmup period. Output characteristics may change if the laser is run at a different power level.

Q-Switched: Specifications are based on the laser pulsing at the specified design frequency. Output characteristics may change if the laser is run at a different frequency.

Specifications Page 2:

This spec sheet has been generated specifically for part number BALR5XXXX, per your request, and data for the entire series is also displayed for your reference. The specs which are specific to BALR5XXXX have been highlighted below in **red + bold**.

Laser Form Factor

Power Supply Options:

The Horizon series of self-levelling alignment lasers are battery-operated. The BALR2 requires two alkaline or Ni-MH AA batteries. The BALR5 requires four alkaline or Ni-MH AA batteries. The BALG5 includes a rechargeable 4000 mAh lithium-ion battery pack, which is recharged via an included microUSB cable and wall adaptor. The BALG5 can also run on four alkaline or Ni-MH AA batteries.


Regulatory Classification:

The model you have selected (BALR5XXXX) requires the following safety label(s):



Accessories:

The most popular accessories for model BALR5XXXX are shown below. For additional details regarding these or other accessories please see our website or contact us directly.

| Part Number | Description | |
|--|--|---------------------|
|  ATP006XXX | 1.2 Meter Elevator Tripod 5/8-11 Thread For Horizon Laser Levels Full Details: www.laserglow.com/ATP | |
| Image Coming Soon! BAMLR0XXX | Red Line Receiver for 5 Line Laser Levels Full Details: www.laserglow.com/BAM | Included With Laser |
| Image Coming Soon! ARLMSXXX | Magnetic Support for Laser Levels Full Details: www.laserglow.com/ARL | Included With Laser |
| Image Coming Soon! ARLMCTXXX | Magnetic Ceiling Target for Laser Levels Full Details: www.laserglow.com/ARL | Included With Laser |

FOR MORE INFORMATION PLEASE CONTACT:

LASERGLOW TECHNOLOGIES
99 Ingram Dr. Unit B, North York, ON, Canada M6M2L7
Tel. (416) 729-7976 Fax (716) 322-3510
sales@laserglow.com www.laserglow.com

E&OE: Data included in this sheet may be subject to change without notice.

Please confirm critical specifications with our staff prior to ordering.