

LRD-0405 Collimated Diode Laser System

Laserglow Part Number: D40100XSX

This model is listed as **inactive** in our product database. Stock may be limited, and availability is subject to change without notice.



Similar Products:

For information about the other lasers in this product family visit:

<http://www.laserglow.com/D40>

Ordering:

Order Online Now or Request Quote:

<http://www.laserglow.com/D40100XSX>

Series Specifications:

| | |
|--------------------|--------|
| Nominal Wavelength | 405 nm |
| Output Type | CW |
| Laser Source Type | Diode |



Overview:

The LRD-0405 Series of Collimated Diode (Semiconductor) Lasers are ideal for applications requiring a short wavelength of 405 nm and output power levels from 5 mW to 500 mW with a high level of long-term output power stability.

These lasers are commonly used for various scientific applications involving fluorescence excitation, as well as PIV, spectral analysis, and a broad spectrum of other applications. The driver is available as a complete FDA-compliant system or as an O.E.M. component with significantly reduced dimensions.

Available with both on-board and remote on/off control as well as a wide array of output power and stability levels, Laserglow products are currently being used by some of the world's top universities and other prominent research facilities.

Key Features:

- Air cooled - no need for water cooling or external chiller
- Lightweight, compact design
- Efficient Diode Laser technology runs on standard AC power (85 - 264 V, 47 - 63 Hz)
- >10,000 hours continuous maintenance-free operating life
- FDA CDRH Compliant Class IIb / Class IV enclosure
- 48-hour replacement coverage available for an additional fee on specific models

Specifications:

This spec sheet has been generated specifically for part number D40100XSX, per your request, and data for the entire series is also displayed for your reference. The specs which are specific to D40100XSX have been highlighted below in **red + bold**.


| | | | |
|--|-------------------------------|-----------------------------|--|
| Output Power (mW) | >10, >30, >50 | >30, >50 | >30, >50, >100 , >200, >300, >400, >500, >800, >1000 |
| Output Power Stability (%RMS/4h) | <1, <3 | <1, <3 | <1, <3, <10 |
| Central Wavelength (nm) | 405 | 406.4 | 406.4 |
| Wavelength Tolerance (+/- nm) | 5 | 5 | 5 |
| Divergence (mrad, full angle) | <1 | <0.5 | <0.5 , <2.5x1 |
| Beam Dimensions (mm, 1/e ²) | 1 | 2.5 | 3x2.7, 4 |
| Transverse Mode | | | <499 mW Near TEM00 >499 mW Multimode |
| Warm-up Time (minutes) | 5 | 15 | 5 |
| Spectral Linewidth (nm) | | <0.06 | <1.2 |
| M ² | <1.2 | | |
| Polarization Ratio | | >50 | >50 |
| Beam Pointing Stability (mrad) | <0.05 | | <0.05 |
| Operating Temperature Range (°C) | 10 to 35 | 20 to 30 | 10 to 35 |
| Max. Analog Modulation Freq. (Hz) | 30000 | 30000 | 30000 |
| Max. TTL Modulation Freq. (Hz) | 30000 | 30000 | 10000 , 30000 |
| Modulation Input Signal | 0-5 VDC | 0-5 VDC | 0-5 VDC |
| Total Power Consumption (W) | 9 | | 6, 9, 10 , 15 |
| Max. Power Input Duty Cycle | 100% | 100% | 100% |
| Standard Warranty (months) | 12 | 12 | 12 |
| MTTF (operational hours) | 10000 | 10000 | 10000 |
| Weight of Product or Laser Head (kg) | 0.6 | 0.8 | 0.6 |
| Beam Height from Base Plate (mm) | 24.8 | 30 | 24.8 |
| Dimensions of Product or Laser Head (mm) | 140.7 (l) x 73 (w) x 46.2 (h) | 122.5 (l) x 65 (w) x 50 (h) | 140.7 (l) x 73 (w) x 46.2 (h) |


CW: All specifications are based on performance at full output power and after the specified warmup period. Output characteristics may change if the laser is run at a different power level.


Q-Switched: Specifications are based on the laser pulsing at the specified design frequency. Output characteristics may change if the laser is run at a different frequency.

Power Supply Options:

These lasers are available with several different power supply options. The model that you have selected is highlighted below, and any other options are shown for easy reference.

| | | | |
|--|--------------------------|----------------------------|-----------------------------|
| | Power Supply Type: | FR | FE |
| FDA-Compliant LabSpec  | Input Power | 85v to 264v | 85v to 264v |
| | Power Supply Weight (kg) | 1.5 | 6.2 |
| | Dimensions (mm) | 154 (l) x 155 (w) x 95 (h) | 320 (l) x 300 (w) x 123 (h) |

| | | |
|---|--------------------------|-----------------------------------|
| | Power Supply Type: | SR |
| FDA-Compliant Standard  | Input Power | 85v to 264v |
| | Power Supply Weight (kg) | 1.2 |
| | Dimensions (mm) | 133 (l) x 130 (w) x 65 (h) |


| | | |
|--|--------------------------|-----------------|
| | Power Supply Type: | R |
|  | Input Power | v to v |
| | Power Supply Weight (kg) | |
| | Dimensions (mm) | (l) x (w) x (h) |

*Power supply may not be exactly as shown, see dimensional drawings on next 2 pages.

*Dimensions for fiber-integrated (I_) include laser head packaged inside.

Regulatory Classification:


The model you have selected (D40100XSX) requires the following safety label(s):



Dimensional Drawing - Laser Form Factor: R:



Dimensional Drawing - Power Supply Form Factor: SR:



Accessories:

The most popular accessories for model D40100XSX are shown below. For additional details regarding these or other accessories please see our website or contact us directly.

| Part Number | Description | |
|--|--|---------------------|
|  AGF5327XX | LSG-532-NF-7 Fit-Over Safety Goggles 532nm Output: OD 7+ at 190-532 nm CE Certified Full Details: www.laserglow.com/AGF | |
|  ACFVISHXA | FC/PC Fiber Coupler/Collimator for visible spectrum wavelengths (400 to 700 nm) (installed and aligned) 11mm diameter input lens Full Details: www.laserglow.com/ACF | |
|  ACSVISHXA | SMA-905 Fiber Coupler/Collimator for visible spectrum wavelengths (400 to 700 nm) (installed and aligned) 11mm diameter input lens Full Details: www.laserglow.com/ACS | |
|  ACALBMXXX | Carrying Case-102 Holds Lab/OEM M, R and S size, standard or LabSpec laser Full Details: www.laserglow.com/ACA | Included With Laser |
|  AFS2002XX | Armored Fiber With SMA 905 Connectors 200um Core Multimode 2 m length Full Details: www.laserglow.com/AFS | |
|  AFF2002XX | Armored Fiber With FC/PC Connectors 200um Core Multimode 2m length Full Details: www.laserglow.com/AFF | |

FOR MORE INFORMATION PLEASE CONTACT:

LASERGLOW TECHNOLOGIES
99 Ingram Dr. Unit B, North York, ON, Canada M6M2L7
Tel. (416) 729-7976 Fax (716) 322-3510
sales@laserglow.com www.laserglow.com

E&OE: Data included in this sheet may be subject to change without notice.

Please confirm critical specifications with our staff prior to ordering.