

Laserglow Product Series Datasheet

SafetyCast



Overview:

Safety Cast Systems are the ideal solution for adding bright, visual warnings in areas where conventional wall and floor markings are easily missed or obstructed. Features include high-output lamps and rugged construction. Floor spot projections are perfect for heavy traffic areas that do not show markings in certain lighting conditions or due to wear. A line projection outlines a safety warning around heavy equipment and machinery where additional safety is required.

Key Features:

- *Color Options:* Red/Green/Blue
- *Expected Life:* 50,000 hours
- *Projection Type:* Dot/Line/Arrow
- *Package Includes:* LED mounted into enclosure with bracket

The Hazard Safety Projection Series was developed to address the safety concerns in warehouses, dock and loading areas, or any industrial workplace area where heavy mobile equipment shares workspace with pedestrians. These products were researched and developed by Laserglow in conjunction with some of the leading lighting manufacturers in the industry. Some of the products in this series are also ideal guidance systems for dock approach, load stacking and off-loading.

Specifications:

This spec sheet has been generated specifically for part number HSC-SC6, per your request, and data for the entire series is also displayed for your reference. The specs which are specific to HSC-SC6 have been highlighted below in **red + bold**.


Total Power Consumption (W)	6	6	9	18	27	72, 120, 135
Projection Type (See below for detail)	Spot	Arrow	Beacon	Line	Spot	Line Spot
Projection Fan Angle (°, full angle)*	6			100	6	6, 50
Brightness (Lux, at 5m / 15")	to	to	to	to	to	to
IP rating	65	65	65	65	65	65
Storage Temperature Range (°C)	-20 to 40	-20 to 40	-20 to 40	-20 to 40	-20 to 40	-20 to 40
Standard Warranty (months)	12	12	12	12	12	12
MTTF (operational hours)	50000	50000	50000	50000	50000	50000
Weight (kg)	1.4	1.4	1.4	2	2.3	5.4
Power Supply	10-80 VDC Input	10-80 VDC Input	10-80 VDC Input	10-80 VDC Input	10-80 VDC Input	10-80 VDC Input

All specifications are based on performance at full power . Output characteristics may change if the product is run at reduced power.

* Other projection angles are available upon request. Contact our sales team if your application requires different projection angles.

Accessories:

The most popular accessories for model HSC-SC6 are shown below. For additional details regarding these or other accessories please see our website or contact us directly.

Part Number	Description	
Image Coming Soon! APH25VAXX	SafetyCast Class 2 Power Supply 25W Full Details: www.laserglow.com/APH	
 HSTCRB1XX	Smart Trigger kit with Single Beam Break Photoelectric Sensor Full Details: www.laserglow.com/HST	
Image Coming Soon! APH90VAXX	SafetyCast Class 2 Power Supply 90W Full Details: www.laserglow.com/APH	

FOR MORE INFORMATION PLEASE CONTACT:

LASERGLOW TECHNOLOGIES
873 St. Clair Ave West, Toronto, ON, Canada M6C1C4
Tel. (416) 729-7976 Fax (480) 247-4864
sales@laserglow.com www.laserglow.com

E&OE: Data included in this sheet may be subject to change without notice.
Please confirm critical specifications with our staff prior to ordering.