

Laserglow Product Datasheet

LQS-3800 Passively Q-Switched Laser System

Laserglow Part Number:
Q3G0203SX



Similar Products:

For information about the other lasers in this product family visit:

<http://www.laserglow.com/Q3G>

Ordering:

Order Online Now or Request Quote:

<http://www.laserglow.com/Q3G0203SX>

Series Specifications:

Nominal Wavelength	3800 nm
Output Type	Q-Switched
Laser Source Type	DPSS



Overview:

The LQS-3800 Series of Diode-Pumped Solid-State (DPSS) Q-Switched Lasers are ideal for applications requiring a very high peak power or short pulse duration at 3800 nm.

These lasers are commonly used for Raman spectroscopy, material processing, and a broad range of other applications. The driver is available as a plug-and-play benchtop system or an O.E.M. component designed for system integration.

Key Features:

- Pulse energy of 7 uJ - 20 uJ
- Pulse repetition rate of 5 kHz - 15 kHz
- Pulse duration in the range of 5-10 ns
- Air cooled
- Runs on standard AC power (85 - 264 V, 47 - 63 Hz)
- 10,000 hour maintenance-free operating life (Expected)
- FDA/CDRH compliant Class IV enclosure

Package Includes:

- Laser Head
- Driver/Power Supply
- Power Cable
- BNC Connector (LabSpec models only)
- Keys, Safety Interlock
- Hard-shell Carrying Case

Specifications:

This spec sheet has been generated specifically for part number Q3G0203SX, per your request, and data for the entire series is also displayed for your reference. The specs which are specific to Q3G0203SX have been highlighted below in **red + bold**.


Output Power (mW)	>100, >200, >300
Single Pulse Energy (μJ)	7, 13, 20
Optimal Pulse Frequency (Hz)	15000
Output Power Stability (%RMS/4h)	<3 , <5, <10
Central Wavelength (nm)	3800
Wavelength Tolerance (+/- nm)	20
Divergence (mrad, full angle)	<1.5
Beam Dimensions (mm, 1/e ²)	3
Warm-up Time (minutes)	10
Avg. Pulse Duration (ns)	5
Approximate Peak Power (W)	4000, 5000, 6000
Operating Temperature Range (°C)	10 to 35
Max. TTL Modulation Freq. (Hz)	20000
Minimum Pulsing Frequency (Hz)	5000
Modulation Input Signal	0-5 VDC
Max. Power Input Duty Cycle	100%
Standard Warranty (months)	12
MTTF (operational hours)	10000
Weight of Product or Laser Head (kg)	2.6
Beam Height from Base Plate (mm)	68.2
Dimensions of Product or Laser Head (mm)	240 (l) x 99 (w) x 94 (h)

CW: All specifications are based on performance at full output power and after the specified warmup period. Output characteristics may change if the laser is run at a different power level.

Q-Switched: Specifications are based on the laser pulsing at the specified design frequency. Output characteristics may change if the laser is run at a different frequency.

Power Supply Options:

These lasers are available with several different power supply options. The model that you have selected is highlighted below, and any other options are shown for easy reference.


	Power Supply Type:	SN
	Input Power	85v to 264v
	Power Supply Weight (kg)	2.3
	Dimensions (mm)	238 (l) x 146 (w) x 102 (h)

*Power supply may not be exactly as shown, see dimensional drawings on next 2 pages.

*Dimensions for fiber-integrated (I_) include laser head packaged inside.

Regulatory Classification:

The model you have selected (Q3G0203SX) requires the following safety label(s):



Dimensional Drawing - Laser Form Factor: N:



Dimensional Drawing - Power Supply Form Factor: SN:



Accessories:

The most popular accessories for model Q3G0203SX are shown below. For additional details regarding these or other accessories please see our website or contact us directly.

Part Number	Description	
-------------	-------------	--

FOR MORE INFORMATION PLEASE CONTACT:

LASERGLOW TECHNOLOGIES

99 Ingram Dr. Unit B, North York, ON, Canada M6M2L7

Tel. (416) 729-7976 Fax (716) 322-3510

sales@laserglow.com www.laserglow.com

E&OE: Data included in this sheet may be subject to change without notice.

Please confirm critical specifications with our staff prior to ordering.