

## LSS-1064 Single-Longitudinal-Mode DPSS Laser System



### Series Specifications:

|                    |         |
|--------------------|---------|
| Nominal Wavelength | 1064 nm |
| Output Type        | CW      |
| Laser Source Type  | DPSS    |

### Overview:

The LSS-1064 Series of Single-Frequency, Single Longitudinal Mode Diode-Pumped Solid-State (DPSS) Lasers are ideal for applications requiring extremely long temporal coherence and an extremely narrow spectral linewidth. This series of 1064 nm SLM lasers are available from 50 mW to 10 W and maintain a high level of long-term output power stability and long operating lifetime at an aggressively competitive cost.

These lasers are commonly used for various scientific purposes such as holography / interferometry, biological experiments, communications research, and a broad spectrum of other applications. The driver is available as a complete FDA-compliant system or as an O.E.M. component with significantly reduced dimensions.

Laserglow products are currently being used by some of the World's top universities and other prominent research facilities.

### Key Features:

- Air cooled - no need for water cooling or external chiller
- Spectral linewidth 0.000001 nm
- Lightweight, compact design
- Efficient DPSS technology runs on standard AC power (85 - 264 V, 47 - 63 Hz)
- >10,000 hours continuous maintenance-free operating life
- FDA CDRH Compliant Class IIIb / Class IV enclosure
- 48-hour replacement coverage available for an additional fee on specific models

### Package Includes:

- Laser Head
- Driver/Power Supply
- Power Cable
- BNC Connector (LabSpec models only)
- Keys, Safety Interlock
- Hard-shell Carrying Case

## Specifications:

This spec sheet has been generated specifically for part number SA6-E, per your request, and data for the entire series is also displayed for your reference. The specs which are specific to SA6-E have been highlighted below in **red + bold**.


|   |  |  |
|---|--|--|
| Output Power (mW)                               | >50, >100, >200, >300, >500, >800, >1000 | <b>&gt;1500, &gt;2000, &gt;5000, &gt;8000, &gt;10000</b> |
| Output Power Stability (%RMS/4h)                | <1, <3, <5                               | <b>&lt;1, &lt;3, &lt;5</b>                               |
| Central Wavelength (nm)                         | 1063.2                                   | <b>1063.2</b>  |
| Wavelength Tolerance (+/- nm)                   | 1  | <b>1</b>   |
| Divergence (mrad, full angle)                   | <1.5                                     | <b>&lt;1.5</b>   |
| Beam Dimensions (mm, 1/e <sup>2</sup> )         | 2  | <b>1.5</b>   |
| Warm-up Time (minutes)                          | 10                                       | <b>10</b>  |
| Optical Noise Amplitude (%RMS @ 20 Hz - 20 MHz) | <0.5                                     | <b>&lt;0.5</b>   |
| Spectral Linewidth (nm)                         | <9.5E-6                                  | <b>&lt;1.0E-5</b>  |
| M <sup>2</sup>                                  | <1.5                                     | <b>&lt;1.2</b>   |
| Polarization Ratio                              | >100                                     | <b>&gt;100</b>   |
| Coherence Length (m)                            | >120                                     | <b>&gt;100</b>   |
| Beam Pointing Stability (mrad)                  | <0.05                                    | <b>&lt;0.05</b>  |
| Operating Temperature Range (°C)                | 15 to 35                                 | <b>10 to 35</b>  |
| Total Power Consumption (W)                     | 35                                       |  |
| Max. Power Input Duty Cycle                     | 100%                                     | <b>100%</b>  |
| Standard Warranty (months)                      | 12                                       | <b>12</b>  |
| MTTF (operational hours)                        | 10000                                    | <b>10000</b>   |
| Weight of Product or Laser Head (kg)            | 0.6                                      |  |
| Beam Height from Base Plate (mm)                | 24.8                                     | <b>58</b>  |
| Dimensions of Product or Laser Head (mm)        | 140.8 (l) x 73 (w) x 46.2 (h)            | <b>427 (l) x 190 (w) x 83 (h)</b>                        |

CW: All specifications are based on performance at full output power and after the specified warmup period. Output characteristics may change if the laser is run at a different power level.

Q-Switched: Specifications are based on the laser pulsing at the specified design frequency. Output characteristics may change if the laser is run at a different frequency.

## Power Supply Options:

These lasers are available with several different power supply options. The model that you have selected is highlighted below, and any other options are shown for easy reference.

|   | Power Supply Type:       | <b>SM</b>                  | <b>SW</b>                          |
|---|--------------------------|----------------------------|------------------------------------|
| <br>FDA-Compliant Standard | Input Power              | 85v to 264v                | <b>85v to 264v</b>                 |
|   | Power Supply Weight (kg) | 1.2                        | <b>5.1</b>                         |
|   | Dimensions (mm)          | 133 (l) x 130 (w) x 65 (h) | <b>307 (l) x 168 (w) x 123 (h)</b> |

\*Power supply may not be exactly as shown, see dimensional drawings on next 2 pages.





\*Dimensions for fiber-integrated (I\_) include laser head packaged inside.

## Regulatory Classification:

The model you have selected (SA6-E) requires the following safety label(s):



**Dimensional Drawing - Power Supply Form Factor: SW:**



UNLESS OTHERWISE SPECIFIED:  
 DIMENSIONS ARE IN MM(INCH)  
 TOLERANCES: +/- 0.75 MM

THE INFORMATION CONTAINED IN THIS  
 DRAWING IS THE SOLE PROPERTY OF  
 LASERGLOW TECHNOLOGIES. ANY  
 REPRODUCTION IN PART OR AS A WHOLE  
 WITHOUT THE WRITTEN PERMISSION OF  
 LASERGLOW TECHNOLOGIES IS  
 PROHIBITED. © 2012 LASERGLOW.COM  
 LIMITED. ALL RIGHTS RESERVED

Laserglow Technologies








TITLE:  
**Power Supply**  
**SW/SY**

REV  
**1**

SCALE: 1:4 SHEET 1 OF 1

## Accessories:

The most popular accessories for model SA6-E are shown below. For additional details regarding these or other accessories please see our website or contact us directly.

| Part Number   | Description   |                     |
|---|---|---------------------|
| <br>AGFA647XX   | LSG-1064-NF-7 Fit-Over Safety Goggles 1064nm<br>Output: OD 7+ at 950-1070 nm<br>CE Certified<br>Full Details: <a href="http://www.laserglow.com/AGF">www.laserglow.com/AGF</a>  |                     |
| <br>ACFMIRHXA   | FC/PC Fiber Coupler/Collimator for IR wavelengths (1000 to 1300 nm) (installed and aligned)<br>11mm diameter input lens<br>Full Details: <a href="http://www.laserglow.com/ACF">www.laserglow.com/ACF</a>               |                     |
| <br>ACSMIRHXA   | SMA-905 Fiber Coupler/Collimator for IR wavelengths (1000 to 1300 nm) (installed and aligned)<br>11mm diameter input lens<br>Full Details: <a href="http://www.laserglow.com/ACS">www.laserglow.com/ACS</a>             |                     |
| <br>ACALBMXXX   | Carrying Case-102<br>Holds Lab/OEM M, R and S size, standard or LabSpec laser<br>Full Details: <a href="http://www.laserglow.com/ACA">www.laserglow.com/ACA</a>   | Included With Laser |
| <br>AFF2002XX | Armored Fiber With FC/PC Connectors 200um Core Multimode 2m length<br>Full Details: <a href="http://www.laserglow.com/AFF">www.laserglow.com/AFF</a>  |                     |
| <br>AFS2002XX | Armored Fiber With SMA 905 Connectors 200um Core Multimode 2 m length<br>Full Details: <a href="http://www.laserglow.com/AFS">www.laserglow.com/AFS</a>   |                     |
| <br>TBK       | Complete optics kits with breadboard mounting hardware.<br>External modulators, variable attenuators, free-space fiber launch systems<br>Full Details: <a href="http://www.laserglow.com/TBK">www.laserglow.com/TBK</a> |                     |

## FOR MORE INFORMATION PLEASE CONTACT:

LASERGLOW TECHNOLOGIES  
 99 Ingram Dr. Unit B, North York, ON, Canada M6M2L7  
 Tel. (416) 729-7976 Fax (716) 322-3510  
[sales@laserglow.com](mailto:sales@laserglow.com) [www.laserglow.com](http://www.laserglow.com)

E&OE: Data included in this sheet may be subject to change without notice.

Please confirm critical specifications with our staff prior to ordering.